

PRODUCT-DETAILS

3KDE175511L9300

AI930S Analog Input, HART (AI4H-Ex)



General Information

Product ID3KDE175511L9300ABB Type DesignationAl930SCatalog DescriptionAl930S Analog Input, HART (Al4H-Ex)

The remote S900 I/O system can be installed in non-hazardous areas or directly in Zone 1 or Zone 2 hazardous area depending on the selected system variant. S900 I/O communicates with the control system level using PROFIBUS DP standard. The I/O system can be installed directly in the field, therefore the costs for mashalling and wiring are reduced.

The system is sturdy, error-tolerant and easy to service. Integrated disconnection mechanisms allow replacement during operation, meaning that there is no need to interrupt the primary voltage in order to exchange the power supply units.

S900 I/O type S. For installation in hazardous area Zone 1. For connecting intrinsically safe field devices installed in Zone 2 or Zone 1 or Zone 0.

AI930S Analog Input (AI4H-Ex), input and power supply for 4...20 mA loop powered 2wire transmitters.

Long Description

- ATEX Certification for installation in Zone 1
- Redundancy (Power and Communication)
- Hot Configuration in Run
- Hot Swap functionality
- Extended Diagnostic
- Excellent configuration and diagnostics via FDT/DTM
- G3-coating for all components
- Simplified maintenance with auto-diagnostics
- Power supply for 4...20 mA loop powered 2-wire transmitters
- Short and break detection
- Electrical isolation between input / bus and input / power
- Common return for all inputs
- 4 channels
- Transmission of HART frames via the fieldbus

- Cyclic HART variables

Additional Information

 Medium Description
 AI930S Analog Input, HART (AI4H-Ex)

 Product Type
 I-O_Module

Ordering

Country of OriginGermany (DE)Customs Tariff Number8538909999

Dimensions

Product Net Length
Product Net Height
Product Net Width
Product Net Wight

104 mm
Product Net Width
104 mm
Product Net Weight

Technical

Number of Channels 4
Channel Type Al
Number of Input 4
Channels

Classifications

3KDE175511L9300 3

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
Number of Batteries	0
RoHS Status	Following EU Directive 2011/65/EU

Categories

 $\textbf{Control System Products} \rightarrow \textbf{I/O Products} \rightarrow \textbf{S900 I/O} \rightarrow \textbf{S900 I/O} \cdot \textbf{Modules} \rightarrow \textbf{Al930S Analog Input} \rightarrow \textbf{Al930S Analog Input}$ Control Systems \rightarrow 800xA \rightarrow I/Os \rightarrow S900 I/O \rightarrow I/O Modules Control Systems \rightarrow 800xA \rightarrow I/Os \rightarrow S900 I/O \rightarrow I/O Modules

