



Discrete I/O Modules (Input)

Input modules provide the interface between the PLC and external input devices such as proximity sensors, push buttons, switches, and BCD thumbwheels. Output modules provide the interface between the PLC and external output devices such as contactors, interposing relays, BCD displays and indicator lamps. GE offers a variety of modules that support different voltage ranges and types, current capacity, isolation and response time to meet your application needs.

	IC694ACC300	IC694MDL230	IC694MDL250	IC694MDL231	IC694MDL240
Product Name	PACSystems RX3i DC Voltage Input Simulator, 8/16 Points	PACSystems RX3i AC Voltage Input Module, 120 VAC Isolated, 8 Point Input	PACSystems RX3i AC Voltage Input Module, 120 VAC Isolated, 16 Point Input	PACSystems RX3i AC Voltage Input Module, 240 VAC Isolated, 8 Point Input	PACSystems RX3i AC Voltage Input Module, 120 VAC, 16 Point Input
Lifecycle Status	Active	Active	Active	Active	Active
Module Type	Input Simulator	Discrete Input	Discrete Input	Discrete Input	Discrete Input
Backplane Support	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1	1	1
Input Voltage Range	N/A	0-132 VAC	0-132 VAC	0-264 VAC	0-132 VAC
Input Current (mA)	N/A	14.5	14.5	15	12
Number of Points	16	8	16	8	16
Response Time (ms)	20 on/30 off	30 on/45 off	30 on/45 off	30 on/45 off	30 on/45 off
Trigger Voltage	N/A	74-132	74-132	148-264	74-132
Points per Common	16	1	1	1	16
Diagnostic Supported	N/A	N/A	N/A	N/A	N/A
Connector Type	Switches	Terminal Block (20 screws), included with module.	IC694TBBx32 or IC694TBSx32. Sold Separately.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.
Internal Power Used	120 mA @ 5 VDC	60 mA @ 5 VDC	60 mA @ 5 VDC	60 mA @ 5 VDC	90 mA @ 5 VDC