



Communications processor CP 443-1; 2x 10/100 Mbit/s (IE switch); RJ45 ports; ISO; TCP; UDP; PROFINET IO controller; S7 communication; Open communication (SEND/ RECEIVE); S7 routing; IP configuration via DHCP/ Block; IP Access Control List; Time synchronization; extended web diagnostics; Fast Startup; Support for PROFINergy;

transfer rate	
transfer rate	
<ul style="list-style-type: none"> <li>at the 1st interface</li> </ul>	10 ... 100 Mbit/s
interfaces	
number of interfaces / acc. to Industrial Ethernet	2
number of electrical connections	
<ul style="list-style-type: none"> <li>at the 1st interface / acc. to Industrial Ethernet</li> </ul>	2
type of electrical connection	
<ul style="list-style-type: none"> <li>at the 1st interface / acc. to Industrial Ethernet</li> </ul>	RJ45 port
design of the removable storage / C-PLUG	No
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
relative symmetrical tolerance / at DC	
<ul style="list-style-type: none"> <li>at 5 V</li> </ul>	5 %
consumed current	
<ul style="list-style-type: none"> <li>from backplane bus / at DC / at 5 V / typical</li> </ul>	1.4 A
power loss [W]	7.25 W
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> <li>during transport</li> </ul>	0 ... 60 °C -40 ... +70 °C -40 ... +70 °C
relative humidity	
<ul style="list-style-type: none"> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-400 single width
width	25 mm
height	290 mm
depth	210 mm
net weight	0.7 kg
product features, product functions, product components / general	
number of units	
<ul style="list-style-type: none"> <li>per CPU / maximum</li> <li>note</li> </ul>	14 max. 4 as PN IO ctrl.

performance data / open communication	
number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	64
data volume	
<ul style="list-style-type: none"> <li>as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	8 Kibyte
<ul style="list-style-type: none"> <li>as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	8 Kibyte
<ul style="list-style-type: none"> <li>as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	8 Kibyte
<ul style="list-style-type: none"> <li>as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	2 Kibyte
number of possible connections / for open communication	
<ul style="list-style-type: none"> <li>by means of T blocks / maximum</li> </ul>	64
data volume	
<ul style="list-style-type: none"> <li>as user data per ISO on TCP connection / for open communication / by means of T blocks / maximum</li> </ul>	1452 byte
performance data / S7 communication	
number of possible connections / for S7 communication	
<ul style="list-style-type: none"> <li>maximum</li> </ul>	128; when using several CPUs
<ul style="list-style-type: none"> <li>with PG connections / maximum</li> </ul>	2
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	128
performance data / PROFINET communication / as PN IO controller	
product function / PROFINET IO controller	Yes
number of PN IO devices / on PROFINET IO controller / operable / total	128
number of PN IO IRT devices / on PROFINET IO controller / operable	64
number of external PN IO lines / with PROFINET / per rack	4
data volume	
<ul style="list-style-type: none"> <li>as user data for input variables / as PROFINET IO controller / maximum</li> </ul>	4 Kibyte
<ul style="list-style-type: none"> <li>as user data for output variables / as PROFINET IO controller / maximum</li> </ul>	4 Kibyte
<ul style="list-style-type: none"> <li>as user data for input variables per PN IO device / as PROFINET IO controller / maximum</li> </ul>	1433 byte
<ul style="list-style-type: none"> <li>as user data for output variables per PN IO device / as PROFINET IO controller / maximum</li> </ul>	1433 byte
<ul style="list-style-type: none"> <li>as user data for input variables per PN IO device / for each sub-module as PROFINET IO controller / maximum</li> </ul>	240 byte
<ul style="list-style-type: none"> <li>as user data for output variables per PN IO device / for each sub-module as PROFINET IO controller / maximum</li> </ul>	240 byte
product functions / management, configuration, engineering	
product function / MIB support	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>SNMP v1</li> </ul>	Yes
<ul style="list-style-type: none"> <li>DCP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>LLDP</li> </ul>	Yes
configuration software	
<ul style="list-style-type: none"> <li>required</li> </ul>	STEP 7 V5.5 SP3 or higher / STEP 7 Professional V12 (TIA Portal) or higher
product functions / diagnostics	
product function / web-based diagnostics	Yes
product functions / switch	
product feature / switch	Yes

product function	
• switch-managed	No
• with IRT / PROFINET IO switch	Yes
• configuration with STEP 7	Yes
<b>product functions / redundancy</b>	
product function	
• ring redundancy	Yes
• redundancy manager	Yes
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
<b>product functions / security</b>	
product function	
• password protection for Web applications	No
• ACL - IP-based	Yes
• ACL - IP-based for PLC/routing	No
• switch-off of non-required services	Yes
• blocking of communication via physical ports	Yes
• log file for unauthorized access	No
<b>product functions / time</b>	
product function / SICLOCK support	Yes
product function / pass on time synchronization	Yes
protocol / is supported	
• NTP	Yes
<b>further information / internet-Links</b>	
Internet-Link	
• to website: Industrial communication	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
• to website: Industry Mall	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
• to website: Information and Download Center	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
• to website: Image database	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
• to website: CAx-Download-Manager	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <a href="http://www.siemens.com/industrialsecurity">http://www.siemens.com/industrialsecurity</a> . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <a href="http://support.automation.siemens.com">http://support.automation.siemens.com</a> . (V3.4)

last modified:

12/16/2020 