BENTLY NEVADA MODEL-SPECIFIC PRODUCT

84510-30

84510-30 is a Bently Nevada Armored Transducer Cable. This independent manual keeps the exact model visible and summarizes product-specific information recorded for procurement and configuration review.

PRODUCT FAMILY	PRODUCT TYPE
Seismoprobe cables	**Armored Transducer Cable**

Exact model configuration

CONFIGURATION FIELD	DECODED VALUE
Displayed model	**84510-30**
Manufacturer	**Bently Nevada**
Product family	**Seismoprobe cables**
Product type	**Armored Transducer Cable**
Cable code: 84510 / 30	**Armored Seismoprobe cable; 30 ft (9.144 m)**
Conductors and ends	**2-wire shielded 22 AWG; 2-socket female end and terminal lugs**
Published family range	**3 to 70 ft; exact assembly temperature rating to be verified**

Application fit

- Connect only to the compatible Seismoprobe and instrument termination.
- Plan the 30 ft cable route with service access and mechanical support.
- Check the actual cable temperature rating independently of the sensor rating.

PRODUCT-SPECIFIC REFERENCE	INSTALLATION NOTE
Armored Seismoprobe cable; 30 ft (9.144 m) 2-wire shielded 22 AWG; 2-socket female end and terminal lugs 3 to 70 ft; exact assembly temperature rating to be verified	This high-temperature cable-family listing does not establish a numeric temperature limit for the offered assembly. Obtain the applicable manufacturer rating.

MODEL-SPECIFIC ENGINEERING REFERENCE

Before ordering 84510-30

Use this page as a controlled procurement checklist. It does not replace the manufacturer datasheet, installation instructions or approval certificate.

Ordering limits and selected values

CONFIGURATION FIELD	DECODED VALUE
Manufacturer	**Bently Nevada**
Product family	**Seismoprobe cables**
Product type	**Armored Transducer Cable**
Cable code: 84510 / 30	**Armored Seismoprobe cable; 30 ft (9.144 m)**
Conductors and ends	**2-wire shielded 22 AWG; 2-socket female end and terminal lugs**
Published family range	**3 to 70 ft; exact assembly temperature rating to be verified**

Procurement checklist

- Confirm the complete ordering code 84510-30 and readable nameplate before shipment.
- Compare the female connector and terminal lugs with installed connections.
- Inspect the armor, cable marking and termination condition.
- Verify the intended shield wiring and receiving instrument configuration.
- Record continuity and restored channel response under site procedures.

DIRECT SALES INQUIRY

Send the full model **84510-30**, quantity, delivery country, and a clear nameplate or installation photo.

Sandy Lin | plcinfo@mooreplc.com | WhatsApp /Phone: +86 18020776786

Source and document status

Technical basis	Baker Hughes / Bently Nevada 141626 Rev. V, cable ordering tables.
Publisher	Moore Automation - independent industrial automation supplier.
Document status	Independent product manual; not a manufacturer-issued datasheet, conformity certificate or calibration certificate.
Important	Verify availability, revision status, compatibility, nameplate data and regulatory requirements before ordering.