FOXBORO I/A SERIES EXACT-MODEL PRODUCT

FBM204 P0916AGOC

FBM204 P0916AGOC identifies a Foxboro I/A Series FBM204 analog input/output interface used with the P0916AG termination-assembly family. The FBM204 provides four isolated analog input channels and four isolated analog output channels. The supplied OC suffix must be retained and verified from the nameplate because the cited manufacturer sheet does not decode that suffix.

PRODUCT FAMILY	PRODUCT TYPE
I/A Series Standard 200 I/O	**0-20 mA Analog I/O Interface Module**

Exact model configuration

CONFIGURATION FIELD	VERIFIED VALUE / CHECK
Displayed model	**FBM204 P0916AGOC**
Manufacturer	**Foxboro**
Product family	**I/A Series Standard 200 I/O**
Product type	**0-20 mA Analog I/O Interface Module**
Base module	**FBM204**
Associated TA family	**P0916AG / P0916AH / P0916XK**
I/O channels	**4 analog inputs and 4 analog outputs**
Channel range	**0 to 20.4 mA dc**
Input accuracy	**+/-0.03% of span**
Output load	**750 ohm maximum**
Module Fieldbus	**Redundant 2 Mbps**
Power input	**24 V dc, +5% / -10%**
Module dimensions	**102 x 45 x 104 mm; 114 mm high with lugs**
Exact suffix	**OC - verify from supplied nameplate**
Country of origin	**USA**

Application fit

- Use only with the documented FBM204 baseplate, termination assembly, and cable combination.
- Match every visible code, including P0916AG and the supplied OC suffix, before transferring field wiring.
- Record loop scaling and complete channel-by-channel input and output checks after installation.

PRODUCT-SPECIFIC REFERENCE	INSTALLATION NOTE
Manufacturer PSS identifies FBM204 with P0916AG-family termination assemblies; the OC suffix remains a nameplate-verification item.	Confirm baseplate, termination assembly, cable, loop power, polarity, and channel mapping before energizing.

MODEL-SPECIFIC ENGINEERING REFERENCE

Before ordering FBM204 P0916AGOC

Use this page as a controlled procurement checklist. It does not replace the manufacturer instruction sheet, wiring drawing, approval certificate, or site safety procedure.

Ordering limits and selected values

CONFIGURATION FIELD	VERIFIED VALUE / CHECK
Manufacturer	**Foxboro**
Product family	**I/A Series Standard 200 I/O**
Product type	**0-20 mA Analog I/O Interface Module**
Base module	**FBM204**
Associated TA family	**P0916AG / P0916AH / P0916XK**
I/O channels	**4 analog inputs and 4 analog outputs**
Channel range	**0 to 20.4 mA dc**
Input accuracy	**+/-0.03% of span**
Output load	**750 ohm maximum**
Module Fieldbus	**Redundant 2 Mbps**
Power input	**24 V dc, +5% / -10%**
Module dimensions	**102 x 45 x 104 mm; 114 mm high with lugs**
Exact suffix	**OC - verify from supplied nameplate**
Country of origin	**USA**

Procurement checklist

- Photograph the complete FBM204 P0916AGOC nameplate.
- Confirm the exact termination assembly and cable part numbers.
- Back up all eight channel assignments and scaling values.
- Verify 24 V dc power and grounding.
- Loop-check four inputs and four outputs and retain the test record.

DIRECT SALES INQUIRY

Send the full model **FBM204 P0916AGOC**, quantity, delivery country, and a clear nameplate or installed-module photo.

Sandy Lin | plcinfo@mooreplc.com | WhatsApp /Phone: +86 18020776786

Source and document status

Technical basis	Schneider Electric / Foxboro PSS 21H-2Z4 B4, FBM204 0 to 20 mA I/O Interface Module.
Publisher	Moore Automation - independent industrial automation supplier.
Document status	Independent product manual; not a manufacturer-issued datasheet, conformity certificate, or calibration certificate.
Important	Verify the complete nameplate, suffix, carrier or terminal hardware, wiring, approvals, and installed-system compatibility before ordering.